

Acknowledgements

The research described in this paper was performed at the W.M. Keck Center for 3D Innovation at the University of Texas at El Paso (UTEP). The Louise Stokes Alliance for Minority Participation provided further funding through grant HRD-0703584 from the National Science Foundation. The findings and opinions presented in this paper are those of the authors and do not necessarily reflect those of the sponsors of this research.

References:

- Ahn, S., Montero, M., Odell, D., Roundy, S., Wright P.K., (2002). Anisotropic material properties of fused deposition modeling ABS. *Rapid Prototyping*, 8 (4), pp. 248-257.
- Agarwala, M.K., Jamalabad, V.R., Langrana, N.A., Safari, A., Whalen, P.J. and Danforth, S.C., (1996). Structural quality of parts processed by fused deposition. *Rapid Prototyping Journal*, 2 (4), pp. 4-19.
- Bellini, A., Gucerri, S., (2003). Mechanical characterization of parts fabricated using fused deposition modeling. *Rapid Prototyping Journal*, 9 (4), pp. 252-264
- Bunshah, R.F., (1994). *Handbook of deposition technologies for films and coatings: Science, technology and applications*. Westwood, New Jersey, Noyes Publications.
- Chua, C.K., Leong, K.F., Lim, C.S., (2003). *Rapid prototyping: principles and applications*. Singapore, World Scientific Publishing Co.
- Espalin, D., Medina, F., Arcaute, K., Zinniel, B., Hoppe, T., Wicker, R., (2009). Effects of Vapor Smoothing on ABS Part Dimensions. *Proceedings from Rapid 2009 Conference & Exposition*, Schaumburg, IL.
- Koppert, J.J., Beukers, A., (2000). Full composite isotensoid pressure vessels or how composites can compete with steel. *SAMPE Journal*, 36 (6), pp. 8–15.
- Kuppan, T., (2000). *Heat exchanger design handbook*. New York, New York, Marcel Dekker, Inc.
- Lee, C.W., Chua, C.K., Cheah, C.M., Tan, L.H., Feng, C., (2004). Rapid investment casting: direct and indirect approaches via fused deposition modeling. *Springer*, 23, pp. 93-101.
- Nagl, M., Lechleitner, T., (2005). Barrier coatings for medical electronic implants. *Vakuum in Forschung und Praxis, Supplement: Vacuum's Best*, 17 (1), pp. 47-50.
- Rashilla, R.J., (1993). All-composite pressure vessels for natural gas vehicle (NGV) fuel tank. *Proceedings of the Conference for Advanced Composites Technologies*, Dearborn, MI, pp. 8–11.
- Spence, J., Tooth, A.S., (1994). *Pressure vessel design: concepts and principles*, London, SE1 8HN, UK, Chapman & Hall.
- Thrimurthulu, K., Pandey, P.M., Reddy, N.V., (2004). Optimum part deposition orientation in fused deposition modeling. *International Journal of Machine Tools and Manufacture*, 44, pp. 585-594.
- Wohlers, T., (2005). New trends and development in additive fabrication. In Bartolo, P.J. (Eds.), *Virtual Modeling and Rapid Manufacturing* (pp. 3-5), Leiden, The Netherlands: Taylor & Francis/Balkema.
- Wohlers, T., (2011). *Appendices: Direct Appendix E: Material properties. Wohlers Report 2011: State of the Industry*. Fort Collins, CO: Wohlers Associates.
- Zhou, J.G., Kokkengada, M., He, Z., Kim, Y.S., Tseng, A.A., (2004). Low temperature polymer infiltration for rapid tooling. *Materials and Design*, 25 (2), pp. 145-154.