

REVIEWED





























- [7] K. P. Cooper and R. F. Wachter, "On making additive manufacturing a production technology," in 2011, pp. 1593.
- [8] J. Xiong and G. Zhang, "Online Measurement of bead Geometry in Gmaw-based Additive Manufacturing Using Passive Vision," vol. 24, pp. 115103 (7 pp.), 11, 2013.
- [9] K. Zeng, N. Patil, H. Gu, H. Gong, D. Pal, T. Starr and B. Stucker, "Layer by layer validation of geometrical accuracy in additive manufacturing processes," in *24th International Solid Freeform Fabrication Symposium - an Additive Manufacturing Conference, SFF 2013, August 12, 2013 - August 14, 2013*, pp. 76-87.
- [10] N. Akhter, H. Jung, H. Chang and K. Kim, "Determination of elastic modulus of a beam by using electronic speckle pattern interferometry," *Opt. Laser Technol.*, vol. 41, pp. 526-529, 2009.
- [11] R. M. Digilov, "Flexural vibration test of a cantilever beam with a force sensor: fast determination of Young's modulus," *European Journal of Physics*, vol. 29, pp. 589-97, 05, 2008.
- [12] R. M. Digilov and H. Abramovich, "Flexural Vibration Test of a Beam Elastically Restrained at One End: A New Approach for Young's Modulus Determination," *Advances in Materials Science & Engineering*, pp. 329530 (6 pp.), 2013.
- [13] ASTM Standard E1876-01, "Standard test method for dynamic young's modulus, shear modulus, and poisson's ratio by impulse excitation of vibration," ASTM International, West Conshohocken, PA, 2006.
- [14] R. J. Roark and W. C. Young, *Roark's Formulas for Stress and Strain*. New York: McGraw-Hill, 1989.
- [15] (). *Dimension P400 Material Properties* [Dimension P400 Material Properties]. Available: <https://store.amtekcompany.com/products.php?product=Dimension-Standard-ABS-Model-Material-%25252d-P400>.