

REVIEWED

especially advantageous in order to minimize edge and corner rounding. When using the ceramic grinding media RXX 10/15 S, lower intensity levels result in a reduction in grinding effectiveness compared to the highest intensity level; this reduction is, however, slight. Thus, using lower grinding intensity not only offers advantages with respect to dimensional accuracy, but is no less advisable in terms of grinding effectiveness.

Acknowledgements

The authors want to thank all industry partners of the DMRC as well as the federal state of North Rhine-Westphalia and the University of Paderborn for the financial and operational support within the project “Analysis of the FDM Part Quality manufactured with ABS M30 with the focus on the toy industry”.

References

- [1] T. Wohlers: „Wohlers Report 2013 – Additive Manufacturing and 3D Printing State of the Industry“, Annual Worldwide Progress Report, 2013
- [2] A. Gebhart: „Generative Fertigungsverfahren / Rapid Prototyping – Rapid Tooling – Rapid Manufacturing“, Carl Hanser Publisher, München 2007
- [3] I. Gibson, D.W. Rosen, B. Stucker: Additive Manufacturing Technologies; Springer, New York 2010
- [4] A. Bruschetto, V. Giordano, F. Venaioli: „3D roughness profile model in fused deposition modelling“, Rapid Prototyping Journal, Vol. 19 No. 4, pp. 240-252, 2013
- [5] Stratasys – Smoothing FDM Parts: <http://stratasys.com/applications/finishing/smoothing-fdm-parts>
- [6] A. Bagsik, V. Schoeppner, E. Klemp: “FDM Part Quality Manufactured with Ultem*9085”, 14th International Scientific Conference on Polymeric Materials, September 15. – 17.2010, Halle (Saale)
- [7] Jenoptik – Poster Surface Parameters: [http://www.jenoptik.com/cms/jenoptik.nsf/res/Poster_Surface_parameters_EN_10037103.pdf/\\$file/Poster_Surface_parameters_EN_10037103.pdf](http://www.jenoptik.com/cms/jenoptik.nsf/res/Poster_Surface_parameters_EN_10037103.pdf/$file/Poster_Surface_parameters_EN_10037103.pdf)
- [8] B. Vasudevarao, D. P. Natarajan, M. Henderson, A. Razdan: „Sensitivity of RP Surface Finish to Process Parameter Variation“, Proceedings of Solid Free Form Fabrication, Austin TX, USA, pp. 252-258, 2000
- [9] Klaus-Peter Müller: Praktische Oberflächentechnik; Vieweg Publisher, Braunschweig 2003
- [10] Stratasys – Mass-Finishing: <http://stratasys.com/applications/finishing/mass-finishing>
- [11] M. Fischer, V. Schöppner: „Some Investigations Regarding the Surface Treatment of Ultem*9085 Parts Manufactured with Fused Deposition Modeling“, Proceedings of Solid Free Form Fabrication, Austin TX, USA, pp. 805-815, 2013
- [12] H. A. Richard, M. Sander: Technische Mechanik. Festigkeitslehre, Vieweg+Teubner (2008)
- [13] Stratasys – Insight Software 9.0
- [14] DIN EN ISO 4287: Geometrische Produktspezifikation (GPS) – Oberflächenbeschaffenheit: Tastschnittverfahren – Benennungen, Definitionen und Kenngrößen der Oberflächenbeschaffenheit