REVIEWED

- The temperature gradient in the depth direction is much higher than those in width and laser scanning directions since the heat transfer in the depth direction is greatly constrained by the low thermal conductivity of the powder layers.
- The addition of subsequent layers significantly affected the temperature gradient and the melting of previous layers. It only takes few milliseconds to melt the material and cool it to room temperature, which indicated the very fast heating and cooling cycles in SLM.

Acknowledgement

The first author would like to thank the Graduate Council Fellowship at the University of Alabama for the financial support.

References

[1] Waterman, N.A., Dickens, P., 1994, "Rapid Product Development in the USA, Europe and Japan," World Class Design to Manufacture, 1(3), pp. 27-36.

[2] Levy, G.N., Schindel, R., Kruth, J.P., 2003, "Rapid Manufacturing and Rapid Tooling with Layer Manufacturing (LM) Technologies, State of the Art and Future Perspectives," CIRP Annals - Manufacturing Technology, 52(2), pp. 589-609.

[3] Guo, N., Leu, M., 2013, "Additive Manufacturing: Technology, Applications and Research Needs," Frontiers of Mechanical Engineering, 8(3), pp. 215-243.

[4] Vandenbroucke, B., Kruth, J., 2007, "Selective Laser Melting of Biocompatible Metals for Rapid Manufacturing of Medical Parts," Rapid Prototyping Journal, 13(4), pp. 196-203.

[5] Clare, A., Chalker, P., Davies, S., Sutcliffe, C., Tsopanos, S., 2008, "Selective Laser Melting of High Aspect Ratio 3D Nickel-Titanium Structures Two Way Trained for MEMS Applications," International Journal of Mechanics and Materials in Design, 4(2), pp. 181-187.

[6] Hollander, D.A., von Walter, M., Wirtz, T., Sellei, R., Schmidt-Rohlfing, B., Paar, O., Erli, H., 2006, "Structural, Mechanical and in Vitro Characterization of Individually Structured Ti–6Al–4V Produced by Direct Laser Forming," Biomaterials, 27(7), pp. 955-963.

[7] Rochus, P., Plesseria, J.-., Van Elsen, M., Kruth, J.-., Carrus, R., Dormal, T., 2007, "New Applications of Rapid Prototyping and Rapid Manufacturing (RP/RM) Technologies for Space Instrumentation," Acta Astronautica, 61(1–6), pp. 352-359.

[8] Wong, M., Tsopanos, S., Sutcliffe, C., Owen, L., 2007, "Selective Laser Melting of Heat Transfer Devices," Rapid Prototyping Journal, 13(5), pp. 291-297.

[9] Kruth, J.-., Levy, G., Klocke, F., Childs, T.H.C., 2007, "Consolidation Phenomena in Laser and Powder-Bed Based Layered Manufacturing," CIRP Annals - Manufacturing Technology, 56(2), pp. 730-759.

[10] Yadroitsev, I., Gusarov, A., Yadroitsava, I., Smurov, I., 2010, "Single Track Formation in Selective Laser Melting of Metal Powders," Journal of Materials Processing Technology, 210(12), pp. 1624-1631.

[11] Tolochko, N.K., Khlopkov, Y.V., Mozzharov, S.E., Ignatiev, M.B., Laoui, T., Titov, V.I., 2000, "Absorptance of Powder Materials Suitable for Laser Sintering," Rapid Prototyping Journal, 6(3), pp. 155-161.

[12] Gusarov, A., Kovalev, E., 2009, "Model of Thermal Conductivity in Powder Beds," Physical Review B, 80(2), pp. 024202.

[13] Thijs, L., Verhaeghe, F., Craeghs, T., Humbeeck, J.V., Kruth, J., 2010, "A Study of the Microstructural Evolution during Selective Laser Melting of Ti–6Al–4V," Acta Materialia, 58(9), pp. 3303-3312.
[14] Roberts, I.A., Wang, C.J., Esterlein, R., Stanford, M., Mynors, D.J., 2009, "A Three-Dimensional Finite Element Analysis of the Temperature Field during Laser Melting of Metal Powders in Additive Layer Manufacturing," International Journal of Machine Tools and Manufacture, 49(12–13), pp. 916-923.
[15] Dong, L., Makradi, A., Ahzi, S., Remond, Y., 2009, "Three-Dimensional Transient Finite Element Analysis of the Selective Laser Sintering Process," Journal of Materials Processing Technology, 209(2), pp. 700-706.
[16] Hussein, A., Hao, L., Yan, C., Everson, R., 2013, "Finite Element Simulation of the Temperature and Stress Fields in Single Layers Built without-Support in Selective Laser Melting," Materials & Design, 52(0), pp. 638-647.
[17] Patil, R.B., Yadava, V., 2007, "Finite Element Analysis of Temperature Distribution in Single Metallic Powder Layer during Metal Laser Sintering," International Journal of Machine Tools and Manufacture, 47(7–8), pp. 1069-1080.
[18] Morsbach, C., Höges, S., Meiners, W., 2011, "Modeling the Selective Laser Melting of Polylactide Composite Materials," Journal of Laser Applications, 23(1), pp. 012005.
[19] Boivineau, M., Cagran, C., Doytier, D., Eyraud, V., Nadal, M., Wilthan, B., Pottlacher, G., 2006, "Thermophysical Properties of Solid and Liquid Ti-6Al-4V (TA6V) Alloy," International Journal of Thermophysics, 27(2), pp. 507-529.
[20] Ding, J., Colegrove, P., Mehnen, J., Ganguly, S., Sequeira Almeida, P.M., Wang, F., Williams, S., 2011, "Thermo-Mechanical Analysis of Wire and Arc Additive Layer Manufacturing Process on Large Multi-Layer Parts," Computational Materials Science, 50(12), pp. 3315-3322.
[21] Dai, K., Shaw, L., 2004, "Thermal and Mechanical Finite Element Modeling of Laser Forming from Metal and Ceramic Powders," Acta Materialia, 52(1), pp. 69-80.
[22] Verhaeghe, F., Craeghs, T., Heulens, J., Pandelaers, L., 2009, "A Pragmatic Model for Selective Laser Melting with Evaporation," Acta Materialia, 57(20), pp. 6006-6012.
[23] Boyer, R., Collings, E., 1993, "Materials properties handbook: Titanium alloys".
[24] Kruth, J.P., Froyen, L., Van Vaerenbergh, J., Mercelis, P., Rombouts, M., Lauwers, B., 2004, "Selective Laser Melting of Iron-Based Powder," Journal of Materials Processing Technology, 149(1–3), pp. 616-622.
[25] Dai, K., Shaw, L., 2002, "Distortion Minimization of Laser-Processed Components through Control of Laser Scanning Patterns," Rapid Prototyping Journal, 8(5), pp. 270-276.