REVIEWED

[6] Wen, S., and Shin, Y. C., "Modeling of transport phenomena during the coaxial laser direct deposition process," Journal of Applied Physics, 108, 044908, 2010.

[7] Qi, H., Mazumder, J., and Ki, H., "Numerical simulation of heat transfer and fluid flow in coaxial laser cladding process for direct metal deposition," Journal of applied physics, 100, 024903, 2006.

[8] Han, L., and Liou, F., "Numerical investigation of the influence of laser beam mode on melt pool," International journal of heat and mass transfer, 47(19), pp. 4385-4402, 2004.

[9] Safdar, S., Pinkerton, A. J., Li, L., Sheikh, M. A., and Withers, P. J., "An anisotropic enhanced thermal conductivity approach for modelling laser melt pools for Ni-base super alloys," Applied mathematical modelling, 37(3), pp. 1187-1195, 2013.

[10] Kamara, A., Wang, W., Marimuthu, S., and Li, L., "Modelling of the melt pool geometry in the laser deposition of nickel alloys using the anisotropic enhanced thermal conductivity approach," Proceedings of the Institution of Mechanical Engineers, Part B: Journal of Engineering Manufacture, 225(1), pp. 87-99, 2011.

[11] Bernauer, M. K., and Herzog, R., "Optimal control of the classical two-phase Stefan problem in level set formulation," SIAM Journal on Scientific Computing, 33(1), pp. 342-363, 2011.

[12] Volkov, O., and Protas, B., "An inverse model for a free-boundary problem with a contact line: Steady case," Journal of Computational Physics, 228(13), pp. 4893-4910, 2009.

[13] Hinze, M., and Ziegenbalg, S., "Optimal control of the free boundary in a two-phase Stefan problem," Journal of Computational Physics, 223(2), pp. 657-684, 2007.

[14] Vossen, G., and Hermanns, T., "On an optimal control problem in laser cutting with mixed finite-/infinite-dimensional constraints," Journal of Industrial and Management Optimization, 10(2), pp. 503-519, 2014.

[15] Vossen, G., Hermanns, T., and Schüttler, J., "Analysis and optimal control for free melt flow boundaries in laser cutting with distributed radiation," ZAMM-Journal of Applied Mathematics and Mechanics/Zeitschrift für Angewandte Mathematik und Mechanik, 2013.

[16] Volkov, O., Protas, B., Liao, W., and Glander, D. W., "Adjoint-based optimization of thermo-fluid phenomena in welding processes," Journal of Engineering Mathematics, 65(3), pp. 201-220, 2009.

[17] Fathi, A., Khajepour, A., Toyserkani, E., and Durali, M., "Clad height control in laser solid freeform fabrication using a feedforward PID controller," The International Journal of Advanced Manufacturing Technology, 35(3-4), pp. 280-292, 2007.

[18] Toyserkani, E., Khajepour, A., and Corbin, S., "3-D finite element modeling of laser cladding by powder injection: effects of laser pulse shaping on the process," Optics and Lasers in Engineering, 41(6), pp. 849-867, 2004.

[19] Song, L., and Mazumder, J., "Feedback control of melt pool temperature during laser cladding process," Control Systems Technology, IEEE Transactions on, 19(6), pp. 1349-1356, 2011.

[20] Hofman, J., Pathiraj, B., van Dijk, J., de Lange, D., and Meijer, J., "A camera based feedback control strategy for the laser cladding process," Journal of Materials Processing Technology, 2012.

[21] Cao, X., and Ayalew, B., "PDE-based Multivariable Control Input Optimization for Laser-Aided Powder Deposition Processes," Journal of Manufacturing Science and Engineering, under reivew, 2014.

[22] De Oliveira, U., Ocelik, V., and De Hosson, J. T. M., "Analysis of coaxial laser cladding processing conditions," Surface and Coatings Technology, 197(2), pp. 127-136, 2005.

[23] Trötzsch, F., Optimal control of partial differential equations: theory, methods, and applications, American Mathematical Soc., 2010.